

RANCH B



















Fixed bollard, diameter 219 mm, used for long-term access prevention. Can be combined with automatic or semi-automatic bollards.









RANCH B

Break-in proof

Rod treatment

| Code | <u>Ci</u> | Name | Description |
|---------------|------------------|--------------------|---|
| P970081 00001 | 2605555 | RANCH B 219/500 | Fixed bollard used for long-term access prevention. Height 490 mm and diameter 219 mm. Flange included. Painted stainless steel version, RAL 7015. |
| P970081 00003 | 2602716 | RANCH B 219/500 I | Fixed bollard used for long-term access prevention. Height 490 mm and diameter 219 mm. Flange included. AISI 304 stainless steel version. |
| P970081 00002 | 2605556 | RANCH B 219/500 L | Fixed bollard used for long-term access prevention. Height 490 mm and diameter 219 mm. Flange included. Version with lights and painted steel shaft, RAL 7015. |
| P970081 00004 | 2613160 | RANCH B 219/500 LI | Fixed bollard used for long-term access prevention. Height 490 mm and diameter 219 mm. Flange included. Version with lights and AISI 304 stainless steel shaft. |
| P970082 00001 | 2605557 | RANCH B 219/700 | Fixed bollard used for long-term access prevention. Height 700 mm and diameter 219 mm. Flange included. Painted stainless steel version, RAL 7015. |
| P970082 00003 | P970082 00003 | RANCH B 219/700 I | Fixed bollard used for long-term access prevention. Height 700 mm and diameter 219 mm. Flange included. AISI 304 stainless steel version. |
| P970082 00002 | 2605558 | RANCH B 219/700 L | Fixed bollard used for long-term access prevention. Height 700 mm and diameter 219 mm. Flange included. Version with lights and painted steel shaft, RAL 7015. |
| P970082 00004 | 2605559 | RANCH B 219/700 LI | Fixed bollard used for long-term access prevention. Height 700 mm and diameter 219 mm. Flange included. Version with lights and AISI 304 stainless steel shaft. |

| | RANCH B 219/500 | RANCH B 219/500 I | RANCH B 219/500 L | RANCH B 219/500 LI |
|---|-----------------|--------------------------|---|--------------------------|
| Rod height | 490 mm | 490 mm | 490 mm | 490 mm |
| Rod diameter | 219 mm | 219 mm | 219 mm | 219 mm |
| Rod thickness | 5 mm | 5 mm | 5 mm | 5 mm |
| Impact resistance | 15000 J | 15000 J | 15000 J | 15000 J |
| Break-in proof | 150000 J | 150000 J | 150000 J | 150000 J |
| RAL 7015 cataphoresis coatin and paint | | AISI 304 stainless steel | RAL 7015 cataphoresis coating and paint | AISI 304 stainless steel |
| | | | | |
| | RANCH B 219/700 | RANCH B 219/700 I | RANCH B 219/700 L | RANCH B 219/700 LI |
| Rod height | 700 mm | 700 mm | 700 mm | 700 mm |
| Rod diameter | 219 mm | 219 mm | 219 mm | 219 mm |
| Rod thickness | 5 mm | 5 mm | 5 mm | 5 mm |
| mpact resistance 15000 J | | 15000 J | 15000 J | 15000 J |

150000 J

AISI 304 stainless steel



150000 J

RAL 7015 cataphoresis coating

and paint

150000 J

RAL 7015 cataphoresis coating and paint

150000 J

AISI 304 stainless steel







BFT SOLUTIONS

EasyAXS

EASY CONNECT. EASY ACCESS.



The new connectivity solution which boosts the potential of BFT products and services to make access automations smarter and easier to use for both installers and end users.



WITH A SMART SOLUTION FOR ACCESSING THEIR

HOMES

Somfy TaHoma







EASY TO CONNECT









MOBILE MODULE + ANTENNA + SIM















EASY TO CONTROL FOR CUSTOMERS

 \longrightarrow ∞











AN UPDATED VERSION OF U-LINK TO GIVE YOU EVEN MORE FUNCTIONALITY



Scalable

You can add as many devices as you want



Intuitive

Easy to install and to use



Functional

Settings can be controlled and firmware updated remotely using dedicated applications



Practical

Works with or without an internet connection



Flexible

It allows you to create groups of interconnected products

U-Link, the exclusive **BFT** technology platform has evolved to offer improved interaction with the latest generation of technological ecosystems. Its ability to interface with all home access automation access devices has been expanded, meaning it is now a very useful tool for installers. It is also a faster communication protocol with increased security for communicating information.

It allows you to save even more time, checking everything very easily and giving you even more peace of mind.









A NEW AND EVEN MORE SECURE RADIO PROTOCOL




Secure

By transmitting data protected by a cryptographic key



Easy

Pairing a remote control with a receiver can be done easily by scanning the QR code and using the dedicated app



The functions of the **Er Ready** system are incorporated and a new procedure is also available for programming remote controls by scanning a QR CODE and using a special app. All products featuring this technology are REPLAY, so they can transmit the code to another BFT remote control using a combination of keys.



Universal

The radio protocol is also compatible with the previous generation of receivers







INFORMATION REGARDING THE PROTECTION OF THE INDUSTRIAL AND INTELLECTUAL PROPERTY RIGHTS OF BFT. S.p.A. protects its industrial property by depositing trademarks, patents, models and designs. The intellectual property of BFT S.p.A. is protected by copyright law. BFT S.p.A. also protects its know-how by taking measures to protect the technical and commercial information inherent in its company and products. All the products in this catalogue are ORIGINAL BFT MODELS and only BFT S.p.A is authorised to produce them and market them anywhere in the world. All the commercial names in this catalogue are owned by BFT S.p.A., and only BFT S.p.A. is authorised to use them in relation to the corresponding merchandise category. FALSIFIERS WILL BE PROCEEDED AGAINST IN ACCORDANCE WITH BOTH CIVIL AND CRIMINAL LAW. THESE CONDITIONS NOT ONLY GUARANTEE THE INTELLECTUAL PROPERTY RIGHTS OF BFT, BUT ALSO PROTECT CUSTOMERS BY GUARANTEEING THAT THE PRODUCTS THEY ARE PURCHASING ARE ORIGINAL BFT PRODUCTS RESULTING FROM STUDIES AND DESIGNS WITHIN THE BFT COMPANY.