



Be ahead



# PARKING SERVER





# PARKING SERVER



## ESPAS 30 ULTRA



Сервер вместе с программным обеспечением управляет базой данных парковочной системы и включает функцию резервного копирования всех данных.

## PARKING SERVER

Код	Ci	Имя	Описание
FP206001	2606015	PARKING SERVER	Сервер вместе с программным обеспечением управляет базой данных парковочной системы и включает функцию резервного копирования всех данных.
FP206003	2606017	PARKING SERVER EXT TEMP	Сервер для расширенного температурного диапазона (от -20 °C до +80 °C). Сервер вместе с программным обеспечением управляет базой данных парковочной системы и включает функцию резервного копирования всех данных.
P800147	2613222	PARKING SERVER PRO	High performance server for car park management, ideal for systems with high data volumes, together with software concentrators and databases, for wired car parks.

## РЕКОМЕНДУЕМЫЕ ДОПОЛНИТЕЛЬНЫЕ ПРИНАДЛЕЖНОСТИ

	<b>Ср P800171 - Ci 2613478</b> <b>EXTENDED TEMPERATURE 8P SWITCH</b> Ethernet-коммутатор с расширенным температурным диапазоном (от -40 °C до +70 °C), 8 Ethernet-портов.		<b>Ср D112099 - Ci 2605688</b> <b>ETHERNET SWITCH 8P</b> Ethernet-коммутатор, 8 Ethernet-портов.
	<b>Ср D114024 - Ci 2605666</b> <b>ROUTER 4G LTE DUAL SIM EXT.TEMP.</b> Маршрутизатор с двумя SIM-картами (микро SIM) с расширенной температурой (от -40 °C до +70 °C), 4G LTE, 2 Ethernet-порта 10/100 Мбит/с, 1 слот MicroSD, антенны 4G/WIFI, поддержка DIN и блок питания		<b>Ср P800145 - Ci 2605945</b> <b>MONITOR FULL HD 21.5" WITH HDMI CABLE</b> 21.5" Full HD монитор с HDMI кабелем



## ESPAS 30 ULTRA

### РЕКОМЕНДУЕМЫЕ ДОПОЛНИТЕЛЬНЫЕ ПРИНАДЛЕЖНОСТИ

	<p><b>Cp</b> P800157 - <b>Ci</b> 2613225 <b>MOUSE AND KEYBOARD KIT</b></p> <p>Kit includes USB mouse and keyboard, colour black.</p>		<p><b>Cp</b> P800161 - <b>Ci</b> 2613228 <b>ROAD ENCLOSURE WITH INSPECTION PLINTH</b></p> <p>Road enclosure with inspection plinth. Lock with retractable handle and closing at three points. Resistance to weather, ageing and corrosion. Floor mounting frames to order separately. Dimensions: 546 x 1110 x 308 (W x H x D) Max load applicable on bottom wall: 65 kg</p>
	<p><b>Cp</b> P800162 - <b>Ci</b> 2613229 <b>FLOOR MOUNTING FRAMES FOR ROAD ENCLOSURE</b></p> <p>Floor mounting frames for road enclosure in steel with double protection treatment: galvanic treatment covered with a layer of epoxy paint. Screws in AISI 304 stainless steel.</p>		



INFORMATION REGARDING THE PROTECTION OF THE INDUSTRIAL AND INTELLECTUAL PROPERTY RIGHTS OF BFT. BFT S.p.A. protects its industrial property by depositing trademarks, patents, models and designs. The intellectual property of BFT S.p.A. is protected by copyright law. BFT S.p.A. also protects its know-how by taking measures to protect the technical and commercial information inherent in its company and products. All the products in this catalogue are ORIGINAL BFT MODELS and only BFT S.p.A. is authorised to produce them and market them anywhere in the world. All the commercial names in this catalogue are owned by BFT S.p.A., and only BFT S.p.A. is authorised to use them in relation to the corresponding merchandise category. FALSIFIERS WILL BE PROCEEDED AGAINST IN ACCORDANCE WITH BOTH CIVIL AND CRIMINAL LAW. THESE CONDITIONS NOT ONLY GUARANTEE THE INTELLECTUAL PROPERTY RIGHTS OF BFT, BUT ALSO PROTECT CUSTOMERS BY GUARANTEEING THAT THE PRODUCTS THEY ARE PURCHASING ARE ORIGINAL BFT PRODUCTS RESULTING FROM STUDIES AND DESIGNS WITHIN THE BFT COMPANY.